



HOBO Pendant data loggers are economical, waterproof temperature data loggers designed for a variety of short and long-term monitoring applications.

Key Advantages:

- Low-cost temperature, light intensity, and acceleration loggers
- Waterproof housing for wet or underwater use
- Data readout in less than 30 seconds via fast Optic USB interface



BASE-U-1 is recommended with these loggers

HOBO Pendant Loggers

Memory: UA-001-08 — 6,500 measurements
 UA-001-64 — 52,000 measurements
 UA-002-08 — 3,500 temperature & light measurements
 UA-002-64 — 28,000 temperature & light measurements
 Sample rate: 1 second to 18 hours, user-selectable
 Battery life: 1-year (typical)—user-replaceable
 Water Depth Rating: 30m from -20 to 20°C (100' from -40° to 68°F) CE

Temperature

Measurement range: -20° to 70°C (-4° to 158°F) in air
 -20° to 50°C (-4° to 122°F) in water
 Accuracy: ± 0.54°C from 0° to 50°C (0.97°F from 32° to 122°F)
 Resolution (10-bit): 0.1°@ 25°C (0.2°@ 77°F)
 Response Time: 15 minutes (to 90% in airflow of 1 m/s)
 5 minutes (to 90% in water)
NIST-traceable temperature accuracy certification available. (See page 72).

Light Intensity

UA-002-08 & UA-002-64 only
 Designed for general purpose measurement of relative light levels
 Range: 0-323,000 lumens/m² [0-30,000 footcandles (lumens/ft²)]

HOBO Pendant G

Memory: UA-004-64 — 64,000 1-axis measurement
 — 32,000 2-axes measurements
 — 21,333 3-axes measurements
 Sample rate: 100 per second (100 Hz) to 18 hours, user-selectable
 Battery life: 1-year (typical)—user-replaceable
 Operating range: -20° to 70°C (-4° to 158°F) in air
 -20° to 50°C (-4° to 122°F) in water CE

Acceleration






Measurement range: ± 3 G
 Accuracy: ±2.5% FS @ 25°C (77°F)—Factory-calibrated
 Resolution (8-bit): 0.02 G

Tilt/Motion

Measurement range: 0° to 180° from vertical
 Accuracy: ±4.3° @ 90° to ±22.3° @ 0° and 180°
 Resolution (8-bit): ±4.3° @ 90° to ±13° @ 0° and 180°

Supplied in Australia by Instrument Choice
Call our scientists on 1300 737 871
www.instrumentchoice.com.au

HOBO Pendant Comparison

		Temperature w/ Alarm Logger	Temperature w/ Alarm Logger	Temperature/ Light Logger	Temperature/ Light Logger	Acceleration/ Tilt/Motion
						
		UA-001-08	UA-001-64	UA-002-08	UA-002-64	UA-004-64
Number of Channels		1	1	2	2	3
Internal Sensors	Temperature	yes	yes	yes	yes	--
	Light Intensity	--	--	yes	yes	--
	Acceleration	--	--	--	--	yes
Size	cm	5.8 x 3.3 x 2.3	5.8 x 3.3 x 2.3	5.8 x 3.3 x 2.3	5.8 x 3.3 x 2.3	5.8 x 3.3 x 2.3
	inches	2.3 x 1.3 x 0.9	2.3 x 1.3 x 0.9	2.3 x 1.3 x 0.9	2.3 x 1.3 x 0.9	2.3 x 1.3 x 0.9
Hole in mounting bail	mm	3.2	3.2	3.2	3.2	3.2
	inches	0.13	0.13	0.13	0.13	0.13
Weight	grams	18	18	18	18	18
	ounces	0.6	0.6	0.6	0.6	0.6

Complete system requires logger, software and base station or shuttle.

Ordering Information

Data Loggers

HOBO Pendant Temperature w/Alarm	UA-001-08
HOBO Pendant Temperature w/Alarm	UA-001-64
HOBO Pendant Temperature w/Light	UA-002-08
HOBO Pendant Temperature w/Light	UA-002-64
HOBO Pendant Acceleration/Tilt/Motion	UA-004-64

Software

HOBOWare Pro Software (Windows/Mac)	BHW-PRO-CD
HOBOWare Lite Software (Windows/Mac)	BHW-LITE-CD
Pendant Base Station**	BASE-U-1

Optional Communications and Accessories

HOBO U-Shuttle (requires Base Station)*	U-DT-1
HOBO Waterproof Shuttle with Couplers*	U-DTW-1
Solar Radiation Shield***	RS1

* Requires HOBOWare Pro software. See page 52 for details.

** HOBO Waterproof Shuttle or Optic USB Base Station (BASE-U-4) may be used instead of the Pendant Base Station (BASE-U-1) (See pages 70-71 for details).

*** Accurate temperature measurements in sunlight require a radiation shield.

HOBOWare software is available for download via the web. Visit onsetcomp.com for details.

Supplied in Australia by Instrument Choice
 Call our scientists on 1300 737 871
www.instrumentchoice.com.au