

Product Specifications

FlashCheck Digital Lollipop Min/Max Thermometer

Temperature Range	-58°F to 392°F (-50°C to 200°C)
Accuracy	±1°F (-4°F to 302°F), ±0.5°C (-20°C to 150°C) or ±1% whichever is greatest
Sensor	Thermistor
Display Resolution	0.1° between -20° to 200° (°C or °F) otherwise 1°
Display Reading Update	1 second
Display Window Size	.77 in W x .37 in H (19.5 mm W x 9.5 mm H)
Calibration	N.I.S.T. traceable by lot. Adjustable calibration resistor beneath the screw on back
Battery	Button Cell Alkaline
Body Casing	Polycarbonate and ABS plastic
Probe Dimensions	Stainless steel, .14 in. (Dia.) x 7.87 in. (L) (3.5 mm x 200 mm)
Weight	1.25 oz. (35.4 gm)
Waterproof Rating	IP67
Certification	CE Mark, RoHS



Model 11047

Model 11048 [certified]

- °C/°F selectable
- 200 mm (~8") Sharp Tip probe
- Min/Max reading memory
- NIST Traceable Calibration Certificate - Model 11048
- Probe cover with pocket clip on back
- Waterproof housing - completely submersible
- Continuous min/max temperature recording until the user shuts it off to reset

DeltaTrak manufactures products under an ISO 9000 registered quality management system

SS0142 13K1

